

SPEEDFITSplit Phase Field Attachable

RMSpumptools SPEEDFiT is the new benchmark for high-speed, consistently reliable field installations of downhole cable to wellhead and packer penetrators - saving you even more rig time. Requiring minimal parts and training, just a cable prep is required - SPEEDFiT requires no epoxy, no gel and no assembly of parts.

SPEEDFiT is easily adaptable for use with different size cables, resulting in simple redress for re-use with only a minimum of spares required. The system variations suit different tubing sizes and can be adapted to different hanger profiles and existing equipment.

Minimal Space required to suit Tight Bores and Ultra Fast Assembly Time in the Field

Electrical Specification - (values may differ depending on model and materials)

Key Performance Features

Simple, Reliable, Efficient
No Epoxy and No Gel
Minimal Assembly of Parts
Saves Significant Rig Time
Full Range to fit all Cable Sizes
ATEX/IECEx Certified

Max OD of FA Connectors: 31mm Plug and Play Style Assembly

Dual Sealing - retains the exclusive Field Proven RMSpumptools Pressure Barrier Incorporates a combination of metal and elastomeric seals

Fully testable after being installed on the Cable

Experience

The industry's unchallenged number one choice for reliability. Exclusive supplier to the demanding North Sea market for over 20 years.





SPEEDFIT

Simple 3 Stage Installation







STAGE 1Insert the Cable Jumpers into the Tubing Hanger and swage in the correct position.

STAGE 2Attach the Split-Phase Field
Attachable Connectors to the
Cable Jumpers.

STAGE 3
Prepare the downhole cable and store the Breakout Box on the cable, then insert the cable into the Field Attachable Connectors.